



TECHNICAL INFORMATION

| | |
|-------------------------|------------------------|
| Dimensions | 460w x 603d x 725-760h |
| Rack Dimension | 400 x 400 |
| Clear Entry Height | 309 |
| Rinse Water Consumption | 1.8L Per Cycle |

WATER CONNECTIONS

| | |
|-------------------|-----------------|
| Connection Point | 3/4 inch (19mm) |
| Inlet Temperature | 60c Max |
| Flow Rate | 4 L/Min |
| Flow Pressure | 1 - 6 bar |

ELECTRICAL

| | |
|-------------------------|--|
| Single Phase (Standard) | 240v 1P 50Hz - 15amp (TCL 3.2Kw) |
| 3 Phase (Optional) | 415v 3P 50Hz - 15 or 20amp (TCL 7.9Kw) |

GENERAL DATA

| | |
|--------------------|--------------------------------|
| Weight (Net/Gross) | 59/68Kg |
| Tank Capacity | 9.5L |
| Noise Emission | 55dB(A) |
| Cycle Times | 120/90/60 Seconds (Adjustable) |

STANDARD INCLUSIONS

| |
|--------------------------------------|
| 1x 15amp Plug and Lead |
| 1x 1m Flexible Water Connection Hose |
| 1x 1m Flexible Waste Hose |
| 1x 4 Row Glass Basket - 400 x 400 |

STANDARD FEATURES

- Touch display with glass surface
- Vario power warewashing system for adjustable pressure
- Quadruple filtration system with clouding sensor
- Fully insulated
- Drain pump
- Rinse booster pump
- Integrated chemical dosing with storage tanks for rinse aid and detergent